



APx511 Hearing Instrument Audio Analyzer

AP performance for hearing instrument production test



APx511 audio analyzer for hearing instrument production test

Key Features

- Automated routines for IEC60118-7 and ANSI S3.22
- 4 W loudspeaker output
- 0 – 400 mA/m telecoil field strength in Interacoustics TBS25 test chamber
- Microphone input with 24 V DC constant current
- 2 V DC battery simulator with current measurement
- Share tests and results with any APx analyzer
- Built-in test sequencer or API to VB, C#, LabVIEW, MATLAB
- THD <-80 dB @ 4 W into 8 Ω (100 Hz - 10 kHz BW)
- Frequency response ± 0.03 dB (100 Hz - 10 kHz BW)

The APx511 Hearing Instrument Audio Analyzer is designed to meet the needs of hearing instrument manufacturers, providing the specific measurements and I/O required for hearing instrument production test, delivered with Audio Precision's reputation for high performance and reliability.

All APx models use the same software. An R&D department using an APx525 or APx585 can share tests and results with APx511 analyzers on production lines, ensuring faster product design and increased collaboration, with AP reports from Quality Control that are trusted around the world.

IEC60118-7 / ANSI S3.22 function library

APx511 supports a .NET library of functions that automate the tests described in IEC60118-7 and ANSI S3.22. For the production environment, these functions can be called from any .NET capable language (including LabVIEW) to control the APx511's output and measurement settings.

For troubleshooting or test setup, the APx511 can be controlled by the standard APx500 software providing a rich graphical user interface and access to automated reporting, real-time signal monitors, high resolution FFTs and controls for limits & other settings.

In addition to standard audio tests such as level, distortion, frequency response, and attack & release, APx511 can measure battery current using its built-in battery simulator circuit.

Built-in support for test chamber speaker, telecoil & microphone

The APx511 generator includes an in-line 4 watt loudspeaker amplifier (8 ohms) and a telecoil amplifier, allowing >110 dB SPL and up to 400 mA/m field strength from 100 Hz to 10 kHz in a test chamber such as the Interacoustics TBS25.

On the input side, APx511 supplies 24 V DC of constant current through a single BNC for a pre-polarized measurement microphone.

APx511 is a member of the larger APx family, so tests and results can be shared or modified with any APx.

The APx500 software features one-click audio measurements, no-code automation, automatic reporting, real-time scope monitor, 1.2M point FFTs, documented API, PESQ perceptual evaluation measurements and more.

APx R&D models

- | | |
|--------|--|
| APx525 | 2 or 4 channel low noise analog, ideal for very high performance analog design |
| APx585 | 8 or 16 channel low noise analog, ideal for simulating real-world environments |

All R&D models support all I/O options listed to the right.

Digital I/O options

- | | |
|----------------|--|
| Digital Serial | Adds interface for I ² S, TDM, DSP |
| Bluetooth | Adds Bluetooth radio & profile control software for Bluetooth audio test |
| HDMI+ARC | Adds HDMI source, sink, monitor, aux and ARC I/O |
| PDM | Adds direct connectivity for digital MEMS mics & PDM amplifiers |

IEC60118-7 / ANSI S3.22 DLL

AP has written a library of functions that automate the tests described in IEC60118-7 and ANSI S3.22.


Calibrate Microphone	Sets the measurement microphone sensitivity based on the output of an acoustic calibrator.
Level Acoustic Output	Level the acoustic output of sound chamber.
Feedback Check	With no generator on, have the analyzer check for feedback and return a Boolean result indicating if feedback is present.
Peak Gain	Generate a sweep from 200 Hz to 8 kHz at user selected level of 50 or 60 dB SPL. Analyze the results to determine the peak signal level at frequencies from 200 Hz to 8 kHz in 100 Hz steps and the frequency at which it occurs.
HFA Gain Test	Measure the average acoustic gain at 1.0, 1.6, and 2.5 kHz with 50 and 60 dB SPL sine signal.
Peak OSPL90	Generate a sweep from 200 Hz to 8 kHz at 90 dB SPL. Analyze the results to determine the peak signal level at frequencies from 200 Hz to 8 kHz in 100 Hz steps and the frequency at which it occurs.
HFA OSPL90	Measure average level in dB SPL at 1.0, 1.6 and 2.5 kHz with 90 dB SPL sine signal.
Battery Current	Generate sine signal at 65 dB SPL, 1 kHz; wait 500 ms and measure battery current.
EIN (Equivalent Input Noise)	Measure HFA Gain at 50 dB SPL (HFA50). Measure HFA Gain at 0 dB SPL (HFA0). EIN = HFA0 - HFA50.
Distortion	Measure THD w/ 500 Hz & 800 Hz signal at 70 dB SPL; w/ 1.6 kHz signal at 65 dB SPL.
Frequency Response	Generate a sweep from 200 Hz to 8 kHz at user selected level of 50 or 60 dB SPL. Return the level results at frequencies from 200 Hz to 8 kHz in 100 Hz steps.
Input Output Response	Conduct a Stepped Level Sweep at 2 kHz from 50 to 90 dB SPL in steps of 5 dB and return the results.
Attack & Release	Measure attack and release times.
Telecoil Sensitivity	Generate a stepped sine at 31.6 mA/m output and frequencies of 100, 1600 and 2,500 Hz and find the average HI output level.

Accessories

The APx HA-1 2cc coupler (for In-the-Ear models) and HA-2 2cc coupler (for Behind-the-Ear models) meet IEC 126 and are available for use with any 1/2 inch or 14mm measurement microphone. Couplers and measurement microphones are sold separately.

APx511 Statement of Use: The Audio Precision APx511 is not intended to be used as a Medical Device. It is not intended to be used for diagnostic or therapeutic purposes and is not intended to be used in or on the human body. It is not intended to be used by audiologists or for any patient specific use.

Intended Use: The APx511 is intended to be used as the signal source and signal analysis portion of a test system which measures the electrical and acoustical response of a hearing aid device while the device is enclosed in a test chamber during the production process. The Audio Precision APx511 is intended to be used solely by hearing aid manufacturers for the purposes of (1) conducting product research and development, (2) verifying product performance during production for quality control purposes, and (3) verifying performance for hearing aids returned for evaluation or service



All audio & power connections are located on the back of the instrument in line with production test standard practices. The microphone input is a standard BNC connector. The outputs connect via a standard DB-15 connector to reduce cabling errors in the production environment. A DB-15 break-out cable terminating in the required connectors for specific test chambers is provided with each APx511.

APx511 Audio Analyzer Key Specifications

LOUDSPEAKER OUTPUT

Maximum output
4 W RMS into 8 Ω (100 Hz - 10 kHz BW)
THD+N
-80 dB @ 4 W / 8 Ω (100 Hz - 10 kHz BW)
Frequency Response
±0.1 dB (100 Hz - 10 kHz)
Amplitude Accuracy
±0.03 dB (+15° C to +30° C)
Frequency Accuracy
2 ppm

TELECOIL OUTPUT

Maximum output
100 mA RMS up to 20 Ω (100 Hz - 10 kHz BW)
(400 mA/m field strength in Interacoustics TBS25)
Total Harmonic Distortion
-80 dB @ 100 mA into 1 Ω (100 Hz - 10 kHz BW)
Frequency Response
±0.1 dB (100 Hz - 10 kHz)
Frequency Accuracy
2 ppm

BATTERY SIMULATOR

Maximum Current
30 mA
DC Output
Range: 0 to 2V; Resolution: 0.5 mV;
Accuracy: ± (1% + 10 mV)
Output Impedance
4.3 Ω
Current Measurement
Range: 0 to 30mA; Resolution: 10μA;
Accuracy: ± 5%

SO/IEC: I7025 ACCREDITED

Accredited by A2LA for equipment calibration under ISO/IEC: 17025. Calibration report and test data included with all new instruments.



Specifications subject to change.

MICROPHONE INPUT

Connector type
BNC (includes constant current power for a standard pre-polarized measurement microphone. CCP can be also disabled for use with an external microphone power supply)
Power
24 V DC constant current
Maximum Input
8.5 Vrms (equivalent to 151 dB SPL at mic sensitivity of 12.5 mV/PA)
Residual Noise (20 kHz BW)
< 1.3 uV (equivalent to 20 dB SPL at mic sensitivity of 12.5 mV/PA)
Frequency Response
±0.03 dB (100 Hz - 20 kHz)

OTHER MEASUREMENT FEATURES
In addition to IEC60118-7 / ANSI S3.22 tests, APx511 can operate as a fully functional audio analyzer.

Audio measurements

Level, Gain, Frequency response, THD+N, IMD, DC level, Noise, SNR, SINAD, Stepped frequency sweep, Stepped level sweep, Maximum output, PESQ (optional), more.

Real time signal monitors

Level, THD+N, Frequency, scope, FFT

Max FFT length

1248K points

Reporting

PDF, MS Word, CSV, PNG

Measurement recorder

Record all audio measurements continuously up to 160 hours

Measurement technologies

Sine, chirp, multitone

Derived results

Smoothing, min/max/statistics, normalize, invert, compare, offset

API

.NET compatible plus LabVIEW driver



绿测科技有限公司

广州总部：广州市番禺区陈边村金欧大道83号江潮创意园A栋208室

深圳分公司：深圳市龙华区龙华街道 油松社区东环一路1号耀丰通工业园1-2栋2栋607

南宁分公司：广西自由贸易试验区南宁片区五象大道401号五象航洋城1号楼3519号

广州分公司：广州市南沙区凤凰大道89号中国铁建·凤凰广场B栋1201房

电话：020-2204 2442

传真：020-8067 2851

邮箱：Sales@greentest.com.cn

官网：www.greentest.com.cn



微信视频号



绿测科技订阅号



绿测工场服务号