



FLIR MR77

5-in-1 Moisture Meter with METERLiNK®

The FLIR MR77 is an all-in-one moisture meter that helps you manage even the toughest water restoration projects. Rugged design with field replaceable sensors, the MR77 is engineered to help you get more done in less time.

Built to last.

Ruggedness you can trust for years

- Field replaceable temperature and relative humidity sensor
- 2 Meter Drop-Tested rubber overmolded pocket-sized design
- Industry-leading limited lifetime warranty with registration

All the sensors you need.

Convenient all-in-one water damage utility tool

- Features integrated pinless moisture sensor, temperature and relative humidity sensor, and IR thermometer for fast non-contact measurements
- Remote pin-type probe for contact moisture readings
- Calculated metrics based on multi-sensor input: Grains Per Pound or Grains Per Kilogram, Dew Point, Condensation Point, Differential Temperature (IR and Dew Point)

Advanced Documentation.

Create reports quickly and easily

- FLIR Tools Mobile connects the MR77 to your compatible iOS or Android smartphone and tablet
- Bluetooth* METERLiNK® technology wirelessly integrates moisture readings on your image with FLIR Thermal Cameras
- Manually store readings and recall up to 99 measurement points

Features

- 9 Material / Wood Groups, High/Low Humidity & Moisture Alarms, Min/Max, Data Hold, Auto Power Off, Bright White LED Backlight, Battery Status Icon, Store, Recall

Includes

- 9V Battery, User Manual/CD, Temperature/RH Sensor, Wired Pin Probe and Limited Lifetime Warranty



Quickly assess upto 0.75 inches deep in Internal Pinless moisture mode



Integrated IR Thermometer with Laser Pointer to measure surface temperatures

Specifications

Technical Summary	RANGE	BASIC ACCURACY
Pinless Moisture	0 to 99.9	Relative
Pinless Moisture Depth Max	0.75in (19mm)	
Pin Moisture	0 to 99%WME	
Relative Humidity	0 to 99%RH	±2.5%RH
Ambien Sensor Temperature	-18 to 170°F, -28 to 77°C	±3.6°F, 2°C
IR Temperature	-4 to 392°F, -20 to 200°C	±3.5%
IR Distance to Spot Ratio	8 inches away : 1 inch spot size	
IR Emissivity	0.95 (fixed)	
Vapor Pressure	0 to 20.0kPa	±2%

Ordering Information

MR77 Pinless Moisture Meter
 MR77-NIST MR77 with Certificate of Traceability to NIST

Accessories

TA11 Protective Case for CM8x and CM7x Series
 TA55 AC Current Line Splitter
 TA70 CAT IV Insulated Alligator Clips
 TA80 CAT IV Silicone Test Leads
 MR01 Replaceable Temp/RH Sensor
 MR02 Replacement Pin Moisture Probe



View measurements on your tablet with free FLIR Tools Mobile



Optional accessories

绿测科技有限公司

广州总部：广州市番禺区陈边村金欧大道83号江潮创意园A栋208室
 深圳分公司：深圳市龙华区龙华街道 油松社区东环一路1号耀丰通工业园1-2栋2栋607
 南宁分公司：广西自由贸易试验区南宁片区五象大道401号五象航洋城1号楼3519号
 广州分公司：广州市南沙区凤凰大道89号中国铁建·凤凰广场B栋1201房
 电话：020-2204 2442
 传真：020-8067 2851
 邮箱：Sales@greentest.com.cn
 官网：www.greentest.com.cn



微信视频号



绿测科技订阅号



绿测工场服务号